


Freestanding step ladder with safety bridge, single-sided 4026

- Conical, single ladder.
- With spacious, practical tool tray made of high-strength plastic.
- Anti-slip feet.
- Bucket hook with 25 kg load-bearing capacity.
- Steps flush with stile, rounded back of treads.
- Versatile.
- Anodised stiles.
- Dimensions of safety platform 250 x 250 mm.

5 year guarantee



4026




Spacious, practical, folding tool tray



Integrated bucket hook

Safe tool storage



Anti-slip feet

Covered steel hinge

Step width 80 mm

You will find further freestanding tread ladders on pages 24, 34, 35, 41, 42.

S

Number of steps		3	4	5	6	7	8
Stile	approx. mm	55	55	55	55	55	55
Length	approx. m	1.37	1.62	1.87	2.12	2.36	2.61
Vert. height to platform	approx. m	0.65	0.88	1.11	1.35	1.58	1.80
Working height	approx. m	2.15	2.38	2.61	2.85	3.08	3.30
Reach height	approx. m	2.65	2.88	3.11	3.35	3.58	3.80
Total vert. height	approx. m	1.25	1.48	1.71	1.95	2.18	2.40
Width	approx. mm	415	440	465	495	520	545
Width between stiles	approx. m	0.70	0.85	1.00	1.15	1.30	1.50
Weight	approx. kg	4.0	4.7	5.4	6.1	6.8	7.6
EAN code		4019502339477	4019502339484	4019502339491	4019502339507	4019502339514	4019502339521
Order no.		402603	402604	402605	402606	402607	402608

For an explanation of working height/reach height in accordance with BGI 694, see page 10.

Double-sided freestanding step ladder 4024

- Stairway freestanding ladder with 80 mm step depth.
- Steps on both sides.
- Anti-slip feet.
- Steps flush with stile.
- Rounded back of step.
- Safe, strong straps.
- Anodised stiles.

5 year guarantee



Steel joint with plastic cover



Replaceable hinges



Anti-slip plastic feet



4024

You will find further freestanding tread ladders on pages 23, 34, 35, 41, 42.

S

Number of steps		2x3	2x4	2x5	2x6	2x7	2x8
Stile	approx. mm	55	55	55	55	55	55
Length	approx. m	0.78	1.03	1.28	1.53	1.79	2.02
Standing height	approx. m	0.69	0.88	1.12	1.34	1.58	1.81
Working height	approx. m	2.19	2.38	2.62	2.84	3.08	3.31
Reach height	approx. m	2.69	2.88	3.12	3.34	3.58	3.81
Total vert. height	approx. m	0.70	0.90	1.15	1.38	1.61	1.84
Width	approx. mm	410	435	460	485	510	540
Width between stiles	approx. m	0.75	0.90	1.10	1.30	1.50	1.65
Weight	approx. kg	3.6	4.5	5.5	6.7	8.0	8.8
EAN code		4019502339415	4019502339422	4019502339439	4019502339446	4019502339453	4019502339460
Order no.		402406	402408	402410	402412	402414	402416

For an explanation of working height/reach height in accordance with BGI 694, see page 10.