

Freestanding step ladder with safety bridge, single-sided 8026

- Steps on one side.
- High-strength straps as safety locking device from size 8 cm.
- Tool tray and small parts with hanging hooks on side.
- Support section made of double tubing for extra-stable, torsion-resistant behaviour.
- Step depth 8 cm.
- Conical.
- Dimensions of safety bridge 250 x 250 mm.

Additional price for set of spring-loaded castors, self-locking, fitted by Hymer

Spring-loaded castor type	fixed on the stile	swivelling on the stile	fixed on support part	swivelling on support part
EAN code	4019502327207	4019502327214	4019502327047	4019502327054
Order no.	0050434	0050435	0050356	0050357



Additional price for set of braces, rigid, removable, fitted by Hymer

Number of steps	4 + 5	6 + 7	8 + 10	12 + 14
EAN code	4019502327177	4019502327184	4019502327191	4019502327221
Order no.	0050431	0050432	0050433	0050437

Spring-loaded castors and braces as accessories and further accessories may be found from page 162 onwards.

Number of steps		4	5	6	7	8	10	12	14
Stile	approx. mm	71	71	71	71	71	71	71	71
Length	approx. m	1.70	1.95	2.20	2.45	2.70	3.20	3.70	4.20
Standing height	approx. m	0.93	1.16	1.40	1.63	1.85	2.32	2.78	3.25
Working height	approx. m	2.43	2.66	2.90	3.13	3.35	3.82	4.28	4.75
Reach height	approx. m	2.93	3.16	3.40	3.63	3.85	4.32	4.78	5.25
Total vert. height	approx. m	1.55	1.78	2.01	2.25	2.48	2.94	3.40	3.87
Width	approx. mm	480	500	530	550	570	630	680	740
Width between stiles	approx. m	0.90	1.05	1.20	1.35	1.50	1.85	2.20	2.55
Weight	approx. kg	5.8	6.7	7.6	8.6	9.6	12.0	14.5	17.0
EAN code		4019502316119	4019502316126	4019502316133	4019502342316	4019502316140	4019502316157	4019502316164	4019502340107
Order no.		802604	802605	802606	802607	802608	802610	802612	802614

For an explanation of working height/reach height in accordance with BGI 694, see page 10.



You will find further step ladders on pages 23, 24, 34, 35, 42.

Double-sided freestanding step ladder 8024

- Step depth 8 cm.
- Steps on both sides.
- Two high-strength straps as anti-spread device.
- Screwed on joint, therefore replaceable.
- Conical.

Attention: Hinged step (top step) must not be used as standing step from model 8024/2x4 upwards.

Additional price for set of spring-loaded castors, self-locking, fitted by Hymer

S

Spring-loaded castor type	fixed on the stile	swivelling on the stile
EAN code	4019502327207	4019502327214
Order no.	0050434	0050435



8024

You will find further freestanding tread ladders on pages 23, 24, 34, 35, 41.

Additional price for set of braces, rigid, removable, fitted by Hymer

S

Number of steps	2x2	2x3	2x4+2x5	2x6+2x7	2x8+2x9+2x10	2x12
EAN code	4019502327290	4019502327252	4019502327146	4019502327269	4019502327153	4019502327160
Order no.	0050646	0050575	0050428	0050576	0050429	0050430

Spring-loaded castors and braces as accessories and further accessories may be found from page 162 onwards.

S

Number of steps	2x2	2x3	2x4	2x5	2x6	2x7	2x8	2x9	2x10	2x12
Stile approx. mm	71	71	71	71	71	71	71	71	71	71
Length approx. m	0.53	0.77	1.04	1.30	1.53	1.80	2.05	2.28	2.54	3.04
Standing height approx. m	0.20	0.45	0.70	0.90	1.15	1.40	1.60	1.85	2.10	2.55
Working height approx. m	1.70	1.95	2.20	2.40	2.65	2.90	3.10	3.35	3.60	4.05
Reach height approx. m	2.20	2.45	2.70	2.90	3.15	3.40	3.60	3.85	4.10	4.55
Total vertical height approx. m	0.45	0.70	0.95	1.15	1.40	1.65	1.85	2.10	2.30	2.80
Width approx. mm	410	430	450	475	500	525	550	575	600	650
Width between stiles approx. m	0.60	0.80	0.98	1.15	1.30	1.50	1.70	1.95	2.15	2.50
Weight approx. kg	3.2	4.4	5.6	6.8	8.2	9.4	10.5	12.2	13.8	16.5
EAN code	4019502316034	4019502316041	4019502316058	4019502316065	4019502316072	4019502324916	4019502316089	4019502340114	4019502316096	4019502316102
Order no.	802404	802406	802408	802410	802412	802414	802416	802418	802420	802424

For an explanation of working height/reach height in accordance with BGI 694, see page 10.