

Platform ladder 8080

- Step depth 8 cm.
- Platform dimensions 40 x 40 cm.
- Spacious tray for tools and small items with hooks to the side, 45 cm wide.
- Guardrail section 80 cm high with side protection on both sides for a safe working position.
- Braces fitted as standard ensure high stability.
- On request, automatically blocking spring-loaded castors can be mounted on the ladder section/support section.

**5 year
guarantee**



S

Number of steps		4	5	6	8	10	12
Stile	approx. mm	71	71	71	71	71	71
Length	approx. m	1.95	2.20	2.45	2.95	3.45	3.95
Standing height	approx. m	0.95	1.15	1.40	1.85	2.35	2.80
Working height	approx. m	2.45	2.65	2.90	3.35	3.85	4.30
Reach height	approx. m	2.95	3.15	3.40	3.85	4.35	4.80
Total vert. height	approx. m	1.75	2.00	2.20	2.70	3.15	3.60
Width	approx. mm	650	670	700	750	800	850
Width between stiles	approx. m	1.00	1.15	1.30	1.60	1.90	2.20
Weight	approx. kg	9.5	10.5	11.8	14.2	17.0	20.0
EAN code		4019502316171	4019502316188	4019502316195	4019502316201	4019502316218	4019502316225
Order no.		808004	808005	808006	808008	808010	808012

Additional price for set of spring-loaded castors, self-locking, fitted by Hymer

S

Spring-loaded castor type	fixed on the stile	swivelling on the stile	rigid on support part	swivelling on support part
EAN code	4019502327207	4019502327214	4019502327047	4019502327054
Order no.	0050434	0050435	0050356	0050357



Spring-loaded castors as accessories and further accessories may be found from page 162 onwards.

Platform ladder with castors and guardrail 8081

- Step depth 8 cm.
- Platform size 40 x 48.5 cm.
- Handrail on both sides.
- Guardrail height above platform 90 cm.
- Equipped with castors, 100 mm diameter on support side.
- Easy to move by lifting ladder side.
- Especially for applications which do not permit use of platform ladders with a wide chassis or require a close approach to shelves.
- Can be folded for space-saving storage.
- Large 45 cm tray for tools and small parts and hooks for buckets and small devices.



5 year guarantee



8081


The handrail is delivered unassembled but prepared for assembly.

S

Number of steps		4	5	6	7	8	9	10	12
Stile	approx. mm	71	71	71	71	71	71	71	71
Length	approx. m	2.05	2.30	2.55	2.80	3.05	3.30	3.55	4.05
Standing height	approx. m	0.95	1.20	1.40	1.65	1.90	2.10	2.34	2.80
Working height	approx. m	2.45	2.70	2.90	3.15	3.40	3.60	3.84	4.30
Reach height	approx. m	2.95	3.20	3.40	3.65	3.90	4.10	4.34	4.80
Total vert. height	approx. m	1.85	2.10	2.30	2.55	2.80	3.00	3.25	3.70
Width	approx. mm	650	670	700	730	750	780	800	850
Width between stiles	approx. m	1.15	1.30	1.45	1.60	1.75	1.90	2.05	2.35
Weight	approx. kg	10.5	12.0	13.0	14.0	15.0	16.5	17.5	19.5
EAN code		4019502318311	4019502318328	4019502318335	4019502318342	4019502318359	4019502318366	4019502318373	4019502318380
Order no.		808104	808105	808106	808107	808108	808109	808110	808112

Platform ladder, folding 8083

- Non-slip steps 80 mm.
- Non-slip platform 600 x 425 mm.
- Aluminium toe board height 150 mm.
- Load-bearing capacity 150 kg.
- Transport castors.
- With telescoping outrigger from size 4.



**5 year
guarantee**



8083

S

Number of steps		3	4	5	6	7	8
Stile	approx. mm	71	71	71	71	71	71
Length	approx. m	1.90	2.00	2.30	2.60	2.85	3.10
Standing height	approx. m	0.73	0.94	1.12	1.38	1.64	1.89
Working height	approx. m	2.23	2.44	2.62	2.88	3.14	3.39
Reach height	approx. m	2.73	2.94	3.12	3.38	3.64	3.89
Total vert. height	approx. m	1.75	1.95	2.14	2.40	2.66	2.90
Width	approx. mm	590	1880	2030	2250	2400	2660
Width between stiles	approx. m	1.12	1.28	1.41	1.61	1.81	2.01
Folded L x W x H	approx. m	2.20 x 0.60 x 0.45	2.40 x 0.75 x 0.45	2.60 x 0.75 x 0.45	2.90 x 0.75 x 0.45	3.15 x 0.75 x 0.45	3.30 x 0.75 x 0.45
Weight	approx. kg	14.6	21.0	22.2	24.4	26.0	27,8
EAN code		4019502335271	4019502335288	4019502346659	4019502335295	4019502335301	4019502335318
Order no.		808303	808304	808305	808306	808307	808308

Platform ladder, telescopic 8084

- Non-slip rungs 30 x 30 mm.
- Non-slip platform 600 x 425 mm.
- Aluminium toe board height 150 mm.
- Telescoping stabiliser from size 7.
- Load-bearing capacity 150 kg.
- Transport castors.
- Stair adjustment.



5 year
guarantee



8084

S

Number of steps		4	7	10
Stile	approx. mm	71	71	71
Length	approx. m	1.90 - 2.18	2.49 - 3.05	2.83 - 3.67
Standing height	approx. m	0.73 - 0.99	1.26 - 1.78	1.57 - 2.35
Working height	approx. m	2.23 - 2.49	2.76 - 3.28	3.07 - 3.85
Reach height	approx. m	2.73 - 2.99	3.26 - 3.78	3.57 - 4.35
Total vert. height	approx. m	1.74 - 2.00	2.28 - 2.80	2.60 - 3.38
Width	approx. mm	1250 - 1350	2100 - 2470	2360 - 2870
Width between stiles	approx. m	1.31 - 1.53	1.75 - 2.16	1.99 - 2.67
Folded L x W x H	approx. m	2.20 x 0.75 x 0.50	2.80 x 0.75 x 0.50	3.10 x 0.75 x 0.50
Weight	approx. kg	20.3	27.4	30.8
EAN code		4019502335660	4019502335325	4019502335332
Order no.		808404	808407	808410

Work platform, short 8085

- Double-sided working platform with guardrail.
- Manual, clampable locking braces.
- Available with short platform (400 x 550 mm).
- Side-mounted folding stabilisers.
- Maximum load-bearing capacity 150 kg.
- Shipped in individual subassemblies ready for assembly.



5 year
guarantee



8085

Number of steps		3	4	5	6	7
Stile	approx. mm	71	71	71	71	71
Standing height	approx. m	0.70	0.90	1.15	1.40	1.60
Working height	approx. m	2.20	2.40	2.65	2.90	3.10
Reach height	approx. m	2.70	2.90	3.15	3.40	3.60
Total vert. height	approx. m	1.70	1.90	2.15	2.40	2.60
Width	approx. mm	1250	1450	1630	1920	2010
Width between stiles	approx. m	1.05	1.25	1.45	1.60	1.80
Weight	approx. kg	20.0	22.0	25.0	27.0	30.0
EAN code		4019502346994	4019502347007	4019502347014	4019502347021	4019502347038
Order no.		808503	808504	808505	808506	808507

S

Work platform, long 8087


- Long work platform 400 x 1200 mm.
- Shipped in individual subassemblies.
- Ready for assembly.

Number of steps		3	4	5	6	7
Stile	approx. mm	71	71	71	71	71
Standing height	approx. m	0.70	0.90	1.15	1.40	1.60
Working height	approx. m	2.20	2.40	2.65	2.90	3.10
Reach height	approx. m	2.70	2.90	3.15	3.40	3.60
Total vert. height	approx. m	1.70	1.90	2.15	2.40	2.60
Width	approx. mm	1250	1450	1630	1920	2010
Width between stiles	approx. m	1.70	1.90	2.10	2.30	2.45
Weight	approx. kg	34.0	36.0	39.0	41.0	44.0
EAN code		4019502342163	4019502342170	4019502342187	4019502342194	4019502342200
Order no.		808703	808704	808705	808706	808707

S

Hooking platform ladder 8086

- Telescopic hooking platform ladder for working on formwork etc.
- Convenient, safe work thanks to all-round protection.
- Non-slip aluminium platform (600 x 425 mm) and aluminium toeboard (150 mm).
- Aluminium tool tray.
- Internal spacing of hooks 200 mm.



Accessories: Hooking set

- For variable height adjustment of the suspension hooks.
- Adjustment range approx. 400 cm.
- See also accessories on page 186.
- User-assembled using tools.
- Content: 2 profiles including fasteners.
- See also accessories on page 169.

5 year
guarantee



8086

EAN code	4019502340084
Order no.	0053433

S

Number of rungs		9
Stile	approx. mm	71
Standing height	approx. m	1.60-2.35
Working height	approx. m	3.10-3.85
Reach height	approx. m	3.60-4.35
Total vert. height	approx. m	2.60-3.35
Width	approx. mm	650
Width between stiles	approx. m	1.65
Weight	approx. kg	19.6
EAN code		4019502340077
Order no.		808609

S

Mobile stockers' ladder, single-sided 6888

- Platform size 600 x 800 mm.
- Non-slip aluminium steps, 200 mm deep.
- 3-sided guardrail, kneebar and toeboard.
- 4 spring-loaded castors, 125 mm diameter, automatic braking when steps ascended, of which 1 castor on the ladder section has parking brake to secure against movement when platform not loaded.
- Vertical step distance 240 mm.
- Maximum load-bearing capacity 150 kg.

Dispatched in prefabricated components for self assembly.
Handrail from size 6 on recommended, see below for additional cost.

Accessories: Handrail for 6888

Number of steps	4	5	6
EAN code	4019502340121	4019502340138	4019502340145
Order no.	0052479	0051777	0051778

Number of steps	7	8
EAN code	4019502340152	4019502340169
Order no.	0051779	0051780

See also accessories on page 165.

**Available from
March 2011**

**5 year
guarantee**



6888

Number of steps		3	4	5	6	7	8
Stile	approx. mm	73	73	73	73	73	73
Standing height	approx. m	0.75	0.95	1.20	1.45	1.70	1.95
Working height	approx. m	2.25	2.45	2.70	2.95	3.20	3.45
Reach height	approx. m	2.75	2.95	3.20	3.45	3.70	3.95
Total vertical height	approx. m	1.75	1.95	2.20	2.45	2.70	2.95
Width	approx. mm	890	890	890	1070	1200	1200
Distance to wall	approx. mm	155	220	285	350	415	480
Width between stiles	approx. m	1.30	1.50	1.70	1.90	2.10	2.30
Weight	approx. kg	29.5	33.0	36.6	41.0	44.5	49.5
Order no.		688803	688804	688805	688806	688807	688808

Mobile stockers' ladder, double-sided 6889

- Design as stocker's ladder 6888, but with steps on both sides.
- Four spring-loaded castors, 125 mm diameter, automatic braking when steps ascended, of which one castor on the ladder section has parking brake to secure against movement when platform not loaded.
- Load-bearing capacity max. 150 kg.

Dispatched in prefabricated components for self assembly.
Handrail recommended from size 6, 2 pairs required per side, see below for additional cost.

Accessories: Handrail for 6889

Number of steps	4	5	6
EAN code	4019502340121	4019502340138	4019502340145
Order no.	0052479	0051777	0051778

Number of steps	7	8
EAN code	4019502340152	4019502340169
Order no.	0051779	0051780

See also accessories on page 165.

**5 year
guarantee**



6889

**Available from
March 2011**

G

Number of steps	3	4	5	6	7	8
Stile approx. mm	73	73	73	73	73	73
Standing height approx. m	0.75	0.95	1.20	1.45	1.70	1.95
Working height approx. m	2.25	2.45	2.70	2.95	3.20	3.45
Reach height approx. m	2.75	2.95	3.20	3.45	3.70	3.95
Total vertical height approx. m	1.75	1.95	2.20	2.45	2.70	2.95
Width approx. mm	890	890	890	1070	1070	1200
Width between stiles approx. m	1.50	1.75	2.05	2.35	2.60	2.90
Weight approx. kg	38.5	40.0	44.1	49.4	54.0	58.0
Order no.	688903	688904	688905	688906	688907	688908