



**H
Y
M
E
R**


**A strong comeback for
our clients!**

Our ladders for hard workers – now back in full use.

Extraordinary performance – robust, stable and ergonomic on every step.


01

Maximum safety:
4 times greater torsional stability due to D-shape stile concept.



02

Greater stability thanks to 8-fold fully riveted steps.



03

Ergonomic working on steps 80 mm deep.



04

Easy to clean and safe grip thanks to smooth outer surface of carefully produced stiles.



05

Large standing surface thanks to extra large ladder feet riveted to the stile.



Step instead of rung



Made in Germany



Hardliner.

Definitely up to any task.

Step leaning ladder

- Easy mounting of suspension hooks or board through necessary holes.
- Front and rear edges or steps flush with stile.
- Matching accessories are on our website or in our main catalogue.



| | | | | | | | |
|----------------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Number of steps | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
| Stile (approx. mm) | 81 | 81 | 81 | 81 | 81 | 81 | 81 |
| Length (approx. m) | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 |
| Height (approx. m) | 0.45 | 0.78 | 0.91 | 1.14 | 1.37 | 1.61 | 1.84 |
| Reach (approx. m) | 2.45 | 2.78 | 2.91 | 3.14 | 3.37 | 3.61 | 3.84 |
| Width (approx. mm) | 425 | 425 | 425 | 425 | 425 | 425 | 425 |
| Weight (approx. kg) | 3.4 | 4.0 | 4.7 | 5.2 | 5.9 | 6.3 | 6.9 |
| Order no. | 601205 | 601206 | 601207 | 601208 | 601209 | 601210 | 601211 |

Workaholic.

Safeguards itself on all sides.

Stepladder with double-sided access

- Maintenance-friendly hinge elements (prevents dirt deposits).
- Spreader lock with high-strength 20 mm wide Perlon straps.



| | | | | | | | |
|--|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Number of steps | 2x3 | 2x4 | 2x5 | 2x6 | 2x7 | 2x8 | 2x10 |
| Stile (approx. mm) | 81 | 81 | 81 | 81 | 81 | 81 | 81 |
| Length (approx. m) | 0.78 | 1.02 | 1.26 | 1.50 | 1.77 | 2.00 | 2.50 |
| Height (approx. m) | 0.21 | 0.44 | 0.67 | 0.91 | 1.14 | 1.37 | 1.83 |
| Reach (approx. m) | 2.21 | 2.44 | 2.67 | 2.91 | 3.19 | 3.37 | 3.83 |
| Total vertical height (approx. m) | 0.65 | 0.90 | 1.15 | 1.35 | 1.60 | 1.80 | 2.30 |
| Width (approx. mm) | 375/450 | 375/475 | 375/500 | 375/525 | 375/550 | 375/575 | 375/625 |
| Spread width (approx. m) | 0.75 | 0.95 | 1.15 | 1.35 | 1.55 | 1.75 | 2.10 |
| Weight (approx. kg) | 4.6 | 5.7 | 6.9 | 8.1 | 9.5 | 10.8 | 13.7 |
| Order no. | 602406 | 602408 | 602410 | 602412 | 602414 | 602416 | 602420 |

Performer.

Looks good for stepping up.

Stepladder with on-sided access

- Spreader lock with high-strength 20 mm wide Perlon straps (from size 6).
- Deep aluminium storage tray with bucket hanging facility.



| | | | | | | | |
|---|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Number of steps incl. platform | 3 | 4 | 5 | 6 | 7 | 8 | 10 |
| Stile (approx. mm) | 81 | 81 | 81 | 81 | 81 | 81 | 81 |
| Length (approx. m) | 1.45 | 1.70 | 1.95 | 2.22 | 2.45 | 2.70 | 3.20 |
| Height (height up to platform) (approx. m) | 0.68 | 0.91 | 1.14 | 1.37 | 1.60 | 1.84 | 2.30 |
| Reach (approx. m) | 2.68 | 2.91 | 3.14 | 3.37 | 3.60 | 3.84 | 4.30 |
| Total vertical height (approx. m) | 1.33 | 1.56 | 1.79 | 2.02 | 2.25 | 2.49 | 2.95 |
| Width (approx. mm) | 305/450 | 305/475 | 305/500 | 305/525 | 305/550 | 305/575 | 305/625 |
| Spread width (approx. m) | 0.70 | 0.85 | 1.00 | 1.15 | 1.30 | 1.50 | 1.80 |
| Weight (approx. kg) | 5.6 | 5.8 | 6.6 | 8.2 | 9.4 | 10.5 | 12.2 |
| Order no. | 602603 | 602604 | 602605 | 602606 | 602607 | 602608 | 602610 |

hymer-access.com

Hymer-Leichtmetallbau GmbH & Co. KG

Käferhofen 10 | 88239 Wangen | Germany

Tel. +49 (0) 75 22 700-707 | Fax +49 (0) 75 22 700-179

ac.lg@hymer-alu.de | www.hymer-access.com